Adgressor® & Adgressor® with EcoFlex™ System

Rider Scrubbers



FACT SHEET



Flexibility for every kind of clean.

The Advance Adgressor® rider-scrubber with EcoFlex™ System lets you clean green and still meet the highest expectations for clean floors. With the industry's most flexible floor-scrubber technology, you can develop a sustainable cleaning routine and quickly adjust to whatever the job demands. Be prepared to get more out of your budget, clean with less impact to the environment and maintain clean floors when you do.

Operators can quickly and easily select the right blend of pad pressure, water and detergent to tackle any cleaning challenge. Here are just a few of the flexible cleaning modes:

- Water Only Perfect for removing surface dirt and maintaining the clean look of floors. Water-only mode eliminates the impact of detergents on the environment and reduces cleaning costs.
- *Ultra-low Detergent* Well suited for routine cleaning where a small amount of green-certified detergent will do the trick. Water and detergent are dispensed separately at the scrub deck, eliminating solution waste.
- **Standard Detergent** The tough cleaning you expect. At standard detergent, pad pressure and flow rate, you'll have a combination powerful enough to pull stubborn dirt, grease, and oil from the surface.
- Burst of Power For deep, restorative cleaning or unexpected challenges. EcoFlex's
 burst of power temporarily increases your machine's pad pressure, detergent use and
 flow rate at the touch of a button.

The Adgressor is designed as a true industrial rider scrubber with reliability, productivity, and ease of use and maintenance built in. Combining large scrub decks and solution capacities with maneuverability and speed, the Adgressor delivers high productivity. A steel chassis and metal bumpers stand up to tough operating environments while thick high density polyethylene tanks will not dent, crack, or corrode.

The Adgressor with EcoFlex System delivers the flexibility to clean your floors more efficiently. By using a system that cleans like you do, you'll reduce your cost to clean and create a more sustainable cleaning program.

STANDARD FEATURES INCLUDE

- QuickChange[™] deck system
- 42 gallon solution and recovery tanks
- Smart Solutions™
- Powerful drive motor
- One-Touch™ system activation
- Metal bumpers
- Comfortable, ergonomic design
- No-tools maintenance access
- Safe Clear-View™ of cleaning area
- Best-in-class maneuverability
- Mechanical brake

TYPICAL APPLICATIONS INCLUDE

- Food and Beverage
- Distribution/Warehousing
- Manufacturing
- Large Retail/Malls
- Transportation Facilities
- Stadiums and Arenas
- Municipalities
- Universities
- Government Buildings




The Advance Adgressor®, designed with Total Clean™ Technology, is very comfortable and safe to use – by design. The result is increased productivity. The Advance Adgressor® is also designed with features to make it easy to clean up and maintain after cleaning. That reduces the total cost of ownership and drives down the cost of cleaning.



Adgressor® & Adgressor® with EcoFlex™ System

Rider Scrubbers




EcoFlex™ System models have One-Touch™ activation for an on-demand cleaning burst of power.



One-Touch™ activation of scrub system. All systems start and stop with machine motion.



The Advance Adgressor® can Grow with your company. The scrub deck interchangeability allows a larger, more productive scrub deck to be installed to address a growing company's increasing square footage.



The Advance Adgressor® turns within a 63 inch (160 cm) aisle. This improves productivity by allowing the Advance Adgressor® to easily clean smaller aisles than the competition.



Industrial Strength Solutions...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factorytrained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Genuine OEM Parts.

Nilfisk Genuine OEM Parts

Technical Specifications

Scrub Path 28 in (71 cm) 32 in (81 cm) 35 in (89 cm) 38 in (97 cm) Max. Productivity 49,280 ft²/hr 56,320 ft²/hr 61,600 ft²/hr 66,880 ft²/hr Max. Productivity 30,800 ft²/hr 35,200 ft²/hr 38,500 ft²/hr 41,800 ft²/hr at 2.5 mph Solution Tank 42 gal (157 L) 42 gal (157 L) <th>Model</th> <th>Adgressor® 2820</th> <th>Adgressor® 3220</th> <th>Adgressor® 3520</th> <th>Adgressor® 3820</th>	Model	Adgressor® 2820	Adgressor® 3220	Adgressor® 3520	Adgressor® 3820	
at 4.0 mph Max. Productivity 30,800 ft²/hr 35,200 ft²/hr 38,500 ft²/hr 41,800 ft²/hr at 2.5 mph 50lution Tank 42 gal (157 L) 42 gal (157 L) <td< td=""><th>Scrub Path</th><td>28 in (71 cm)</td><td>32 in (81 cm)</td><td>35 in (89 cm)</td><td>38 in (97 cm)</td></td<>	Scrub Path	28 in (71 cm)	32 in (81 cm)	35 in (89 cm)	38 in (97 cm)	
Max. Productivity at 2.5 mph 30,800 ft²/hr 35,200 ft²/hr 41,800 ft²/hr 41,800 ft²/hr Solution Tank 42 gal (157 L) 42 gal (157	Max. Productivity	49,280 ft²/hr	56,320 ft²/hr	61,600 ft²/hr	66,880 ft²/hr	
at 2.5 mph Solution Tank 42 gal (157 L) 42 gal (157	at 4.0 mph					
Solution Tank	Max. Productivity	30,800 ft ² /hr	35,200 ft²/hr	38,500 ft²/hr	41,800 ft²/hr	
Recovery Tank 42 gal (157 L) Brush Drive Disc - 1.5 hp (1) 1.5 hp (1) 0.6 hp (3) 0.6 hp (3) Cylindrical - Two 0.75 hp, 560 Watt motors on opposing ends, poly-V belt brush drive - All Models Scrub Deck Disc - Manual-adjusting side skirts contain solution - All Models Cylindrical - Includes hopper for collecting small litter. Auto-adjusting side skirts contain solution - All Models Brush Speed Disc 250 rpm, Cylindrical 900 rpm - All Models Brush Pressure Programmable 3 settings up to 250 lb (113 kg) - All Models Drive System 1.5 hp motor with gear transmission, band brake and dynamic braking. Programmable speeds up to 4.5 mph (7.3 kph) - All Models Gradeability Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg - All Models Min. Turn-around Aisle Width Voltage 36 Volt for more power and longer run time - All Models	at 2.5 mph					
Brush Drive Disc - 1.5 hp (1) 1.5 hp (1) 0.6 hp (3) 0.6 hp (3) Cylindrical - Two 0.75 hp, 560 Watt motors on opposing ends, poly-V belt brush drive - All Models Scrub Deck Disc - Manual-adjusting side skirts contain solution - All Models Cylindrical - Includes hopper for collecting small litter. Auto-adjusting side skirts contain solution - All Models Brush Speed Disc 250 rpm, Cylindrical 900 rpm - All Models Brush Pressure Programmable 3 settings up to 250 lb (113 kg) - All Models Drive System 1.5 hp motor with gear transmission, band brake and dynamic braking. Programmable speeds up to 4.5 mph (7.3 kph) - All Models Gradeability Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg - All Models Min. Turn-around Aisle Width Voltage 36 Volt for more power and longer run time - All Models						
Disc – 1.5 hp (1) 1.5 hp (1) 0.6 hp (3) 0.6 hp (3) Cylindrical – Two 0.75 hp, 560 Watt motors on opposing ends, poly-V belt brush drive – All Models Disc – Manual-adjusting side skirts contain solution – All Models Cylindrical – Indudes hopper for collecting small litter. Auto-adjusting side skirts contain solution – All Models Brush Speed Disc 250 rpm, Cylindrical 900 rpm – All Models Brush Pressure Programmable 3 settings up to 250 lb (113 kg) – All Models Drive System 1.5 hp motor with gear transmission, band brake and dynamic braking. Programmable speeds up to 4.5 mph (7.3 kph) – All Models Gradeability Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg – All Models Min. Turn-around Aisle Width Voltage 36 Volt for more power and longer run time – All Models	Recovery Tank	42 gal (157 L)	42 gal (157 L)	42 gal (157 L)	42 gal (157 L)	
Cylindrical – Two 0.75 hp, 560 Watt motors on opposing ends, poly-V belt brush drive – All Models Scrub Deck Disc – Manual-adjusting side skirts contain solution – All Models Cylindrical – Includes hopper for collecting small litter. Auto-adjusting side skirts contain solution – All Models Brush Speed Disc 250 rpm, Cylindrical 900 rpm – All Models Brush Pressure Programmable 3 settings up to 250 lb (113 kg) – All Models Drive System 1.5 hp motor with gear transmission, band brake and dynamic braking. Programmable speeds up to 4.5 mph (7.3 kph) – All Models Gradeability Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg – All Models Min. Turn-around Aisle Width Voltage 36 Volt for more power and longer run time – All Models						
Scrub Deck Disc - Manual-adjusting side skirts contain solution - All Models Cylindrical - Includes hopper for collecting small litter. Auto-adjusting side skirts contain solution - All Models Brush Speed Disc 250 rpm, Cylindrical 900 rpm - All Models Brush Pressure Programmable 3 settings up to 250 lb (113 kg) - All Models Drive System 1.5 hp motor with gear transmission, band brake and dynamic braking. Programmable speeds up to 4.5 mph (7.3 kph) - All Models Gradeability Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg - All Models Min. Turn-around Aisle Width Voltage 36 Volt for more power and longer run time - All Models					0.6 hp (3)	
Disc – Manual-adjusting side skirts contain solution – All Models Cylindrical – Includes hopper for collecting small litter. Auto-adjusting side skirts contain solution – All Models Brush Speed Disc 250 rpm, Cylindrical 900 rpm – All Models Brush Pressure Programmable 3 settings up to 250 lb (113 kg) – All Models Drive System 1.5 hp motor with gear transmission, band brake and dynamic braking. Programmable speeds up to 4.5 mph (7.3 kph) – All Models Gradeability Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg – All Models Min. Turn-around 63 inch (160 cm) on a machine with a 32 inch deck – All Models Voltage 36 Volt for more power and longer run time – All Models		Two 0.75 hp, 560 Watt motors on opposing ends, poly-V belt brush drive – All Models				
Cylindrical – Includes hopper for collecting small litter. Auto-adjusting side skirts contain solution – All Models Brush Speed Disc 250 rpm, Cylindrical 900 rpm – All Models Brush Pressure Programmable 3 settings up to 250 lb (113 kg) – All Models Drive System 1.5 hp motor with gear transmission, band brake and dynamic braking. Programmable speeds up to 4.5 mph (7.3 kph) – All Models Gradeability Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg – All Models Min. Turn-around Aisle Width Voltage 36 Volt for more power and longer run time – All Models						
Brush Speed Disc 250 rpm, Cylindrical 900 rpm – All Models Brush Pressure Programmable 3 settings up to 250 lb (113 kg) – All Models Drive System 1.5 hp motor with gear transmission, band brake and dynamic braking. Programmable speeds up to 4.5 mph (7.3 kph) – All Models Gradeability Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg – All Models Min. Turn-around Aisle Width Voltage 36 Volt for more power and longer run time – All Models						
Brush Pressure Programmable 3 settings up to 250 lb (113 kg) – All Models Drive System 1.5 hp motor with gear transmission, band brake and dynamic braking. Programmable speeds up to 4.5 mph (7.3 kph) – All Models Gradeability Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg – All Models Min. Turn-around 63 inch (160 cm) on a machine with a 32 inch deck – All Models Aisle Width Voltage 36 Volt for more power and longer run time – All Models						
Drive System 1.5 hp motor with gear transmission, band brake and dynamic braking. Programmable speeds up to 4.5 mph (7.3 kph) – All Models Gradeability Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg – All Models Min. Turn-around Aisle Width Voltage 36 Volt for more power and longer run time – All Models						
Programmable speeds up to 4.5 mph (7.3 kph) – All Models Gradeability Transport - 20% / 11.5 deg,, Working (scrubbing) - 8% / 4.6 deg – All Models Min. Turn-around Aisle Width Voltage 36 Volt for more power and longer run time – All Models						
Gradeability Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg - All Models Min. Turn-around 63 inch (160 cm) on a machine with a 32 inch deck - All Models Aisle Width Voltage 36 Volt for more power and longer run time - All Models	Drive System					
Min. Turn-around 63 inch (160 cm) on a machine with a 32 inch deck – All Models Aisle Width Voltage 36 Volt for more power and longer run time – All Models						
Aisle Width Voltage 36 Volt for more power and longer run time – All Models						
Voltage 36 Volt for more power and longer run time – All Models		63 inch (160 cm) on a machine with a 32 inch deck – All Models				
Power Source 305 Ah battery package with optional 395 Ah batteries – All Models						
Battery Charger Option of shelf or onboard charger – All Models						
Solution Control Smart Solutions™ is standard providing better water and chemical utilization and fewer dump and refill cycles. – All Models						
Vacuum Motor 0.75 hp 3-stage with optional dual vacuum – All Models						
Sound Level 68 dB A at operator's position – All Models						
Frame Dimensions Length = 61 in (155 cm), Width = 32 in (82 cm), Height = 53 in (135 cm) – All Models	Frame Dimensions					
Squeegee Width 32.6 in (83 cm) 36.6 in (93 cm) 42.1 in (107 cm) 45.1 in (115 cm)	Squeegee Width	32.6 in (83 cm)	36.6 in (93 cm)	42.1 in (107 cm)	45.1 in (115 cm)	
Weight Machine Only 657 lb (298 kg). With full tank and standard batteries 1,553 lb (705 kg) – All Models	Weight	Machine Only 657 lb (298 kg). \	Nith full tank and standard batt	eries 1,553 lb (705 kg) – All Mod	dels	
Optional Adgressor® EcoFlex™ System Specifications						
Solution Flow Pump						
Dilution Ratios 32:1, 50:1, 64:1, 100:1, 128:1, 150:1, 200:1, 256:1, 300:1	Dilution Ratios	32:1, 50:1, 64:1, 100:1, 128:1, 150:1, 200:1, 256:1, 300:1				
Refillable Cartridge Capacity 1.25 gal (4.75 L)	Refillable Cartridge Capacity	1.25 gal (4.75 L)				
Battery Watering System	Battery Watering System					

Specifications are subject to change without notice.



14600 21st Avenue North Plymouth, MN 55447-3408 www.advance-us.com 800-214-7700 Phone:

800-989-6566

Fax:

240 Superior Boulevard Mississauga, Ontario, Canada I 5T 2L2 www.nilfisk-advance.ca 905-564-1149 or 800-668-8400 Phone:

905-564-1030 or 800-263-5111

Printed in U.S.A., Form L1568A 11-13

